# CORRECTED VERSION

### (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 26 May 2005 (26.05.2005)

PCT

(10) International Publication Number WO 2005/047057 A3

(51) International Patent Classification7:

B60N 2/66

(21) International Application Number:

PCT/US2004/036912

(22) International Filing Date:

5 November 2004 (05.11.2004)

(25) Filing Language:

English

(26) Publication Language:

**English** 

(30) Priority Data:


60/519,304

11 November 2003 (11.11.2003)

- (71) Applicant (for all designated States except US): JOHN-SON CONTROLS TECHNOLOGY COMPANY [US/US]; 650 Waverly, Holland, MI 49423 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MICHALAK, Eric, Bernard [US/US]; 34326 Sheridan, Westland, MI 48185 (US). BENZING, Robert, Michael [US/US]; 5161 Blissfield Highway, Britton, MI 49229 (US). HENSEL, David [US/US]; 6427 Connaught Court, Canton, MI 48187 (US).

- (74) Agent: WILKE, James, A.; FOLEY & LARDNER LLP, 777 East Wisconsin Avenue, Milwaukee, WI 53202 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]



a spaced distance from the first transverse member. A compliant back member (60) having a first end operably connected to the first transverse member (46) and a second end operably connected to the second transverse member (44). A biasing member (100) having a first end operatively engaging the compliant back member and a second end being anchored with respect to the back frame wherein when a seat occupant's back applies a force to the compliant back member, the biasing member applies a reaction force.



## WO 2005/047057 A3



### Published:

- with international search report
- (88) Date of publication of the international search report: 10 November 2005
- (48) Date of publication of this corrected version: 22 December 2005

(15) Information about Correction: see PCT Gazette No. 51/2005 of 22 December 2005, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.